


Technical information



Micro Precision 7.28 MK III Tweeter

History.

The 7.28 is a long term, traditional Micro-Precision product. Since year 2001, when MK I was born, we use the same dimension and design.

This consequent way gives the possibility to update or upgrade 10 years old tweeters to the latest technology, used in the 7.28 MK III M2M.

Features :

CNC made aluminium housing.

CNC magnetsystem 1/1000mm tolerance.

Linear : 800Hz-22.000Hz +/-2dB.

Natural dampingwool inside.

Low FS to create perfect 2-way's.

Hexagon grill for best dispersion.

Strong terminal.


Mountingaccessories available.



Technical Data

Height total	48 mm	FS	840 Hz
Outer Diameter	56 mm	Sensitivity	90 dB 2,83V/1m.
Cutout Diameter	40 mm	R-DC	3,5 Ω
Interior Depth	26 mm	Power handling	100 W
Drillcircle	48.5 mm / 120 deg.	Voicecoil	Aluminium
		Voicecoil diameter	28 mm
		Membrane	Coated Silk
		Recommended . Filter	2500 Hz / 6dB
Weight	0.300 kg / Pair	Updated :	9. 2011

Technical information



Micro Precision 7.28 MK III Tweeter



Level	Ohm
	0
-1,5	1
-3,1	2
-4,2	3
-5,3	4
-5,9	5
-7,1	6
-7,8	7
-8,3	8

Also available :
A version in black on
special request.



Also available :
A small version on special
request (7.28or).